Applicants: de Bont, et al. Serial No.: 10/590,860 Filing Date: April 23, 2007

Docket No.: 294-258 PCT/US/RCE

Page 2 of 5

AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions and listings of claims in the application.

Please amend claim 12:

Please cancel claim 26; and

Please withdraw claims 13, 20 and 25.

Listing of claims:

1-11. (Cancelled)

- 12. (Presently amended) A method for extracting a fermentation product selected from the group consisting of 4 hydroxybenzoic acid, benzaldehyde, a catechol, benzylalcohol, einnamic acid, phenol, and mixtures thereof, from a fermentation liquid comprising:
- conducting a fermentation using a biocatalyst to form a fermentation product in a (i) fermentation liquid;
- contacting the fermentation liquid with a solvent-impregnated porous carrier, (ii) wherein the solvent-impregnated porous carrier has a density different from the fermentation liquid and the fermentation product is sorbed by the solvent-impregnated carrier; and
- separating the fermentation product from the solvent-impregnated porous carrier. wherein the fermentation product is selected from the group consisting of 4-hydroxybenzoic acid, benzaldehyde, a catechol, benzylalcohol, cinnamic acid, phenol, and mixtures thereof.
- 13. (Withdrawn) A method according to claim 12, wherein the separation is carried out by steam stripping, back-extraction, heating, or combinations thereof.
- 14. (Withdrawn) A method according to claim 12, wherein the solvent-impregnated porous carrier in step (iii) is recycled through to step (ii).

Applicants: de Bont, et al. Serial No.: 10/590,860 Filing Date: April 23, 2007

Docket No.: 294-258 PCT/US/RCE

Page 3 of 5

 (Previously presented) A method according to claim 12, wherein said solvent impregnated carrier comprises a polymeric carrier.

- (Withdrawn) A method according to claim 15, wherein said polymeric carrier comprises one or more polystyrene, polypropylene, polytetrafluoroethylene, silicone, polyethylene, or regenerated cellulose group.
- 17. (Withdrawn) A method according to claim 16, wherein said polymeric carrier is crosslinked.
- (Withdrawn) A method according to claim 12, wherein said solvent impregnated carrier comprises an inorganic carrier, preferably selected from silica, alumina, aluminosilicates, and combinations thereof
- (Withdrawn) A method according to claim 12, wherein said fermentation product is 4-hydroxybenzoic acid, benzylalcohol, 3-methylcatechol, benzaldehyde, cinnamic acid, or mixtures thereof.
- 20. (Withdrawn) A method according to claim 12, wherein said biocatalyst is selected from Pseudomonas putida, Escherichia coli, Sacharomyces cerevisiae, Lactobacillus species, or Aspergillus niger.
 - 21. (Withdrawn) A method according to claim 12, wherein
 - said solvent impregnated carrier is inserted at or near the bottom of a fermentor containing said fermentation liquid and is collected at or near the top of said fermentor, wherein said solvent impregnated carrier has a density that is lower than that of said fermentation liquid; or

Applicants: de Bont, et al. Serial No.: 10/590,860 Filing Date: April 23, 2007

Docket No.: 294-258 PCT/US/RCE

Page 4 of 5

 - said solvent impregnated carrier is inserted at or near the top of a fermentor containing said fermentation liquid and is collected at or near the bottom of said fermentor, wherein said solvent impregnated carrier has a density that is higher than that of said fermentation liquid.

- 22. (Withdrawn) A method according to claim 12, which is carried out continuously.
- 23. (Withdrawn) A method according to claim 12, wherein said porous solvent impregnated carrier has an average pore diameter of from 2.5 nm to 50 μ m.
- (Withdrawn) A method according to claim 12, wherein the porosity is from 30 to 80%.
- (Withdrawn) A method according to claim 12, wherein the catechol is 3methylcatechol.
 - 26. (Cancelled)
- (Previously presented) A method according to claim 12, wherein said biocatalyst is Pseudomonas putida.
- 28. (Previously presented) A method according to claim 15, wherein said polymeric carrier comprises a polystyrene.
- (Previously presented) A method according to claim 12, wherein the separation is carried out by steam stripping.